ATEX Compliant 2 Port Steam Valve
Steam Valve
Series 56-VND

CE Ex II3G Ex h IIB T3 Gc
-5°C ≤ Ta ≤ +60°C

How to Order

Air operated **56 – VND 2 0 □ D S – □ 15A – □**

ATEX category 3

Body option

Nil	Standard (Copper alloy)
Note) **S**	Stainless steel body

Note) Threaded type only

Thread type

Nil	Rc
F	G
N	NPT
T	NPTF

Options

Nil	None
Note) **B**	With bracket
L	With indicator light(visual verification of operation)
Note) **BL**	With bracket and indicator light(visual verification of operation)

Note) Brackets (for valve size 1/2/3/4 only) will be assembled at the time of shipment.
Bracket part no.
Valve size 1: VN1-A16 (with thread)
Valve size 2 to 4: VN□-16
2 to 4

Valve size / **Valve type** / **Port size**

Symbol	Orifice dia. (mm)	Symbol 0 N.C.	Symbol 2 N.O.	Symbol 4 N.C.	Symbol	Port size Rc
1	ø7	—	●	●	6A	1/8
		—	●	●	8A	1/4
		—	●	●	10A	3/8
2	ø15	●	●	—	10A	3/8
		●	●	—	15A	1/2
3	ø20	●	●	—	20A	3/4
4	ø25	●	●	—	25A	1
5	ø32	●	●	—	32A	1 1/4
		●	●	—	32F	1 1/4 B Flange
6	ø40	●	●	—	40A	1 1/2
		●	●	—	40F	1 1/2 B Flange
7	ø50	●	●	—	50A	2
		●	●	—	50F	2 B Flange

All other specifications are the same as the standard products Series VND.
Click here for details.