

# Conforming to OSHA Standard Pressure Relief 3 Port Valve with Locking Holes (Double Action) **VHS2510/3510/4510/5510 Series**



## How to Order

**Double action**

**VHS 4 510 - [ ] 04 A - BS - [ ] - [ ]**

Pressure relief 3 port valve

**Body size**

Symbol
2
3
4
5

**Double action**

**Thread type**

Nil	Rc
N	NPT
F	G

**Port size**

Symbol	Port size	Body size			
		2	3	4	5
01	1/8	●	—	—	—
02	1/4	●	●	●	—
03	3/8	—	●	●	—
04	1/2	—	—	●	—
06	3/4	—	—	●	●
10	1	—	—	—	●

**Handle / Bonnet material**

Symbol	Material
A	Flame resistant PBT
B	Aluminum

**Made to Order**

Symbol	Description
X1	Body: Red


**Semi-standard specifications**

Symbol	Description
Nil	—
K	Handle color: Black
R	Flow direction: Right → Left
Z <sup>Note)</sup>	psi as unit displayed on label

Note) Only for the NPT thread. Under the New Measurement Law, products for overseas use only (SI unit type for use in Japan).

**Options**

Symbol	Description
Nil	—
B	With bracket
S	Built-in silencer (EXH port)



B: Packed together  
S: Assembled for shipping

SMC validation products have been validated based on ISO 13849-2: 2012 Annex A & B.