

# ATEX Compliant 2 Port Steam Valve

## Steam Valve

# Series 56-VND



CE II3G Ex h IIB T3 Gc  
-5°C ≤ Ta ≤ +60°C

### How to Order

**Air operated** 56-VND 2 0 □ D S - □ 15A - □

ATEX category 3

**Body option**

Nil	Standard (Copper alloy)
Note) S	Stainless steel body

Note) Threaded type only

**Thread type**

Nil	Rc
F	G
N	NPT
T	NPTF

**Options**

Nil	None
Note) B	With bracket
L	With indicator light (visual verification of operation)
Note) BL	With bracket and indicator light (visual verification of operation)

Note) Brackets (for valve size 1/2/3/4 only) will be assembled at the time of shipment.  
Bracket part no.  
Valve size 1: VN1-A16 (with thread)  
Valve size 2 to 4: VN□-16  
    ↑  
    2 to 4

**Valve size**      **Valve type**      **Port size**

Symbol	Orifice dia. (mm)	Symbol			Symbol	Port size Rc
		0 N.C.	2 N.O.	4 N.C.		
1	ø7	—	●	●	6A	1/8
		—	●	●	8A	1/4
		—	●	●	10A	3/8
2	ø15	●	●	—	10A	3/8
		●	●	—	15A	1/2
3	ø20	●	●	—	20A	3/4
4	ø25	●	●	—	25A	1
5	ø32	●	●	—	32A	1 1/4
		●	●	—	32F	1/4 B Flange
6	ø40	●	●	—	40A	1 1/2
		●	●	—	40F	1/2 B Flange
7	ø50	●	●	—	50A	2
		●	●	—	50F	2 B Flange

All other specifications are the same as the standard products Series VND.  
[Click here](#) for details.